

## Hose Clamp with Bolts

for heavier hoses



### Material

- screw: galvanised steel
- band collar: steel, galvanised

### Applications

- Special clamp for connecting medium and heavy duty hoses to connectors on mobile and stationary units

### Properties

- Bis Spannungsbereich 214 - 226 mm mit einem Schloss, ab 230 mm mit 2 Schlössern
- extremely robust
- rust-protected
- bandwidth approx. 20 - 26 mm
- bandwidth approx. 0.8 - 1.6 mm

### Product Variations

clamping range in mm	width x thickness in mm	article no.
214 - 226 mm	25 x 1,8	621-214-115
32-35	20 x 1,0	621-032-115

36-39	20 x 1,0	621-036-115
40-43	20 x 1,0	621-040-115
44-47	22 x 1,0	621-044-115
48-51	22 x 1,0	621-048-115
52-55	22 x 1,0	621-052-115
56-59	22 x 1,0	621-056-115
60-63	22 x 1,0	621-060-115
64-67	25 x 1,5	621-064-115
68-73	25 x 1,5	621-068-115
74-79	25 x 1,5	621-074-115
80-85	25 x 1,5	621-080-115
86-91	25 x 1,5	621-086-115
92-97	25 x 1,5	621-092-115
98-103	25 x 1,5	621-098-115
104-112	25 x 1,5	621-104-115
113-121	25 x 1,5	621-113-115
122-130	25 x 1,5	621-122-115
131-139	25 x 1,5	621-131-115
140-148	25 x 1,5	621-140-115
149-161	25 x 1,8	621-149-115
162-174	25 x 1,8	621-162-115
175-187	25 x 1,8	621-175-115
188-200	25 x 1,8	621-188-115
201-213	25 x 1,8	621-201-115
225-243	25 x 1,8	621-225-115
250-268	25 x 1,0	621-250-115
305-323	25 x 1,0	621-305-115
320-335	25 x 1,0	621-320-115
350-365	25 x 1,0	621-350-115
398-422	25 x 1,0	621-398-115
455-473	25 x 1,0	621-455-115
500-518	25 x 1,0	621-500-115

All data refers to a medium and ambient temperature of +20 °C.

\* Refers to the inner hose lining

Subject to technical changes and colour deviations.

#### Available from stock

- Clamping range from 32/35mm to 500/518 mm

**Available on request**

- Available on request in other sizes and materials.