

## Master-Grip Hose Clamp, screwable

**Special clamp for right-lay hoses**



### Material

- band collar, bridge, housing: steel

### Applications

- Special clamp for lighter and medium duty, right-handed spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR, Master-PVC and Master-SANTO

### Properties

- robust
- easy to install
- rust-protected
- primarily tight and tear-proof connection via bridge profiles

### Product Variations

for right-hand hoses in DN	clamping range in mm	article-no.
38	35-44	533-040-100
40	35-44	533-040-100
45	45-55	533-050-100
50	45-55	533-050-100

55	55-65	533-060-100
60	55-65	533-060-100
65	65-75	533-070-100
70	65-75	533-070-100
75	70-80	533-080-100
80	75-80	533-080-100
90	90-110	533-090-100
100	100-120	533-100-100
110	110-130	533-110-100
120	120-140	533-125-100
125	120-140	533-125-100
130	130-150	533-130-100
140	140-160	533-140-100
150	150-170	533-150-100
160	160-180	533-160-100
170	170-190	533-175-100
175	170-190	533-175-100
180	180-200	533-180-100
200	200-220	533-200-100
215	210-230	533-215-100
225	220-240	533-225-100
250	250-270	533-250-100
275	270-290	533-275-100
300	300-320	533-300-100
315	310-330	533-315-100
325	320-340	533-325-100
350	350-370	533-350-100
375	370-390	533-375-100
400	400-420	533-400-100
450	450-470	533-450-100
500	500-520	533-500-100

All data refers to a medium and ambient temperature of +20 °C.

\* Refers to the inner hose lining

Subject to technical changes and colour deviations.

**Available from stock**

- Clamping range from 35/44 mm to 500/520 mm

**Available on request**

- Available on request in other sizes and materials.